



Class leading products that work together to optimise acoustics

Installation with FlexiFit tabs

Thank you for purchasing acoustic treatment products from Acousti Pro. Please read the information below fully before proceeding with installation.

When you un-package foam products they may be slightly distorted as a result of the packaging and transport. This is perfectly normal and they will return to their original shape over a short space of time.



The adhesive used on the FlexiFit tabs is **pressure sensitive**. Therefore maximum bond strength between tile and tab is achieved by applying good even pressure between the two surfaces. After affixing the tabs you must leave them for **24 hours** BEFORE fitting the tiles to the wall. This will allow the adhesive to cure before it has to support the weight of the tile / trap.

IMPORTANT! Airspace tiles have different profiles on either side. Please take care when affixing FlexiFit tabs as putting them on the wrong side will be difficult to rectify without damaging the tile. We recommend 4 tabs on each S or LV tile (2 at the top; 2 at the bottom) and 6 on the L and XL tiles (3 at the top; 3 at the bottom). Place the tabs approximately 2cm from the edge of the tile as per the photo above. For our bass traps we recommend 12 tabs.

When removing tiles from walls (permanently or for re-positioning) please separate the hook and loop tabs carefully using your fingers to avoid damage to the tile. If you want to remove the remaining tabs from your wall/ceiling a handy tip is to heat them up using a hairdryer making them much easier to remove with less chance of damage to your wall/ceiling.

For portable acoustic treatment please see our Production Buddy™ products including tiles on stands and movable wall systems.

If you are in any doubt regarding any of the above please do not hesitate to contact us for after sales support on **01264 810108**

www.acoustipro.com