

PRX715XLF

15" SELF-POWERED EXTENDED LOW
FREQUENCY SUBWOOFER SYSTEM

COMPACT, ULTRA-LIGHTWEIGHT SYSTEMS... PERFORMANCE YOU CAN TRUST

The PRX715XLF is the next step in the highly successful PRX Series and introduces the first use of JBL's patented Differential Drive® Technology with ferrite drivers. Differential Drive technology incorporates lower mass in the ferrite magnet for reduced weight while maximizing power amp efficiency for greater heat dissipation and increased power handling. Powering the PRX715XLF is a 1500 Watt high performance, exceptionally low distortion amplification system engineered to deliver clean power with maximum headroom to efficiently deliver rich, deep bass response even at very high sound power levels. Compact, ultra-lightweight, the PRX715XLF uses JBL's tour tested technology throughout so you can trust it to deliver a lifetime of reliable performance.

+ **1500 WATT**
HIGH-PERFORMANCE
POWERED SPEAKER SYSTEM

+ **56 LB / 25.4 KG**
FOR EASY PORTABILITY

+ **37 HZ / 113 HZ**
EXTENDED FREQUENCY RANGE

KEY FEATURES

HIGH PERFORMANCE LOW FREQUENCY DRIVERS

Tour tested Differential Drive technology delivers extended frequency response, high power output and low distortion in a dramatically lighter package. With the ferrite magnet positioned inside the dual-coil/dual-gap voice coil, heavy steel pole pieces are eliminated. The heat sink is the chassis itself, further lowering system weight while ensuring consistent, reliable performance.




AMPLIFICATION

Highly efficient Class-D amplification drives Maximum Sound Pressure Levels are the best indication of the performance of a powered speaker and all PRX700 Series excel in this critical specification. JBL's ability to maximize the speaker and amplifier performance guarantees ample power, accurate dynamics and sonic purity.





ROAD TOUGH CONSTRUCTION

Built from a combination of 25 mm (on the top and bottom for added rigidity) and 18 mm, strong, light-weight poplar plywood made structurally sound with tongue and groove joints. JBL's tour proven DuraFlex™ finish, grilles from dent-resistant 16 gauge steel, and light-weight glass-filled nylon handles ensure strength and durability. A seriously rugged package that will withstand the brutality of constant road use.



Hear the truth.





POLARITY

Normal or reverse polarity can be switched for matching to varied sub/satellite system configurations.

CONFIGURATIONS

The PRX700 Series is a platform technology with a range of models that integrate seamlessly for multiple system options that excel in challenging audio environments and loud volumes. Compact and powerful, the PRX715XLF offers exceptional sub/sat performance for its weight and size.

- Pole receptacle accepts a SS3-BK or SS3-BK24 on the top panel
- Integrated stereo pass-thru, with selectable HP filter, and polarity reverse
- Augment full range setups for live performance or DJ
- Multiple cabinets for a scalable, highly professional sound reinforcement system
- Suspend any of the top cabinets for use in commercial installations or Houses of Worship

INPUT PANEL


An integrated limiter circuit on the inputs guarantees signal integrity. System performance is optimized through the use of sophisticated Digital Signal Processing for EQ, crossover, amplifier control, and protection.

- DSP Input limiter circuit, crossover, dynamic limiting, component optimization, selectable system EQ
- 2 x XLR-1/4" combination inputs, with 2 x XLR loop-thru


SPECIFICATION

PRX700


S E R I E S




PRX710




PRX712




PRX715




PRX715XLF



PRX718XLF



PRX725



PRX735

| | PRX710 | PRX712 | PRX715 | PRX715XLF | PRX718XLF | PRX725 | PRX735 |
|--------------------------------|--|--|--|-------------------------------|-------------------------------|--|--|
| System Type: | Self powered 10", two-way, bass-reflex | Self powered 12", two-way, bass-reflex | Self powered 15", two-way, bass-reflex | Self powered 15", bass-reflex | Self powered 18", bass-reflex | Self powered 15", two-way, bass-reflex | Self powered 15", three-way, bass-reflex |
| Max SPL Output: | 133 dB | 135 dB | 136 dB | 131 dB | 134 dB | 139 dB | 136 dB |
| Freq. Range (-10 dB): | 50 Hz - 19.6 kHz | 44.8 Hz - 19.6 kHz | 42.9 Hz - 19.5 kHz | 37 Hz - 113 Hz | 30 Hz - 103 Hz | 42 Hz - 18.5 kHz | 35 Hz - 20 kHz |
| Freq. Response (±3 dB): | 63.5 Hz - 18.5 kHz | 55.7 Hz - 18.2 kHz | 58.1 Hz - 17.2 kHz | 44 Hz - 91 Hz | 35 Hz - 87 Hz | 49 Hz - 17 kHz | 42 Hz - 20 kHz |
| Coverage Pattern: | 100° x 60° nominal | 90° x 50° nominal | 90° x 50° nominal | - | - | 90° x 50° nominal | 90° x 50° nominal |
| Amplifier Design: | Class D | Class D | Class D | Class D | Class D | Class D | Class D |
| Power Rating: | 1500 W | 1500 W | 1500 W | 1500 W | 1500 W | 1500 W | 1500 W |
| Dimensions (mm): | 498.7 x 335.6 x 322.3 | 612.4 x 384.6 x 341.4 | 714.4 x 445. x 358.7 | 547.1 x 445 x 580 | 690.4 x 523.2 x 723.9 | 1070.4 x 445 x 538 | 952.5 x 445 x 538 |
| (H x W x D) (in): | 19.63 x 13.21 x 12.69 | 24.11x 15.14 x 13.44 | 28.13 x 17.52 x 14.12 | 21.54 x 17.52 x 22.48 | 27.18 x 20.6 x 28.5 | 42.14 x 17.52 x 21.18 | 37.5 x 17.52 x 21.18 |
| Net Weight: | 16.4 kg (36 lb) | 19.4 kg (42.5 lb) | 21.6 kg (47.5 lb) | 25.4 kg (56 lb) | 36.8 kg (81 lb) | 37.19 kg (82 lb) | 34.9 kg (77 lb) |